

The P-2240 is power amplifier featuring high performance-to-cost suit for paging applications in schools, churches, offices and retail stores.



Article number:P-2240 CE

Specifications

| | |
|---------------------|--|
| Power source | 220 - 240 V AC, 50 / 60 Hz (or 24 VDC) |
| Rated output | 240 W |
| Frequency response | 50 Hz - 20 kHz |
| Distortion | < 1 % (at 1 kHz, 1/3 rated output power) |
| Power consumption | 520 W (at rated output), 238 W (EN 62368-1) |
| Current consumption | 15,0 A |
| S/N ratio | 60 dB |
| Inputs | Line-in 0 dBV, 10 k Ω , balanced, screw terminal 100 V line in: 40 dBV, 330 k Ω , unbalanced, screw terminal Power remote control: Make contact |
| Outputs | Loop out: 0 dBV, 10 k Ω , balanced, screw terminal Speaker out: Balanced (floating) High impedance: 42 Ω (100 V), 21 Ω (70 V) Low impedance: 4 Ω (31 V) |
| Number of channels | 1 |
| Indicator | Power, signal, peak |
| Certificates | CE |
| Dimensions | 420 x 100.9 x 351.3 mm (W x H x D) |
| Gross weight | 14,5 KG |
| Finish | ABS resin, Steel plate, black, |
| Weight | 13.2 kg |

Appearance

